

# Hot levels, harsh conditions

## Pointek CLS 300 level switch

### Pointek CLS 300

Inverse Frequency Shift capacitance technology results in higher accuracy and resolution.

Patented Active Shield provides superior reliability.

Tank walls, variations in product quality, vapor and dust have a negligible effect on the readings.

Automated Sensor Test program tells you if circuitry and sensor are fully functional. No need to remove the unit from the tank.

Online commissioning of parameters allows for full advantage of sensitivity and accuracy of the instrument: number of counts, set points, adjustable hysteresis, time delay, and output status. Make adjustments from the control room or other remote locations.

A wide range of models available: rod and cable sensors up to 25 meters (82 ft); high temperature up to 400 °C (752 °F); intrinsically safe and explosion proof.



# precision

In harsh process conditions with high chemical and physical abuse, reliability and accuracy are critical for safe and economical operation.


For these conditions, Pointek® CLS 300 is the ideal level switch. It is used for high and low level alarm of interfaces, solids, liquids, slurries and viscous materials. This capacitance switch handles temperatures up to 400 °C (752 °F) and pressures from full vacuum to 35 bar (511 psi).

Pointek CLS 300 applies a unique approach to capacitance technology that is based on extensive field experience. It includes patented Active-Shield and Inverse Frequency Shift technology, ensuring high accuracy, resolution and repeatability.

Pointek CLS 300 – a million in one.

[www.siemens.com/level](http://www.siemens.com/level)

million  
in one



# SIEMENS

# Technical specifications

Pointek CLS 300		
	Analog	Digital
<b>Power</b>	<ul style="list-style-type: none"> <li>■ 12 to 250 V AC/DC, 50/60 Hz</li> <li>■ 2 VA/2 W maximum</li> </ul>	<ul style="list-style-type: none"> <li>■ Standard: 9 to 32 V DC, max. 2 VA/2 W</li> <li>■ Intrinsically safe: 9 to 24 V DC, max. 2 VA/2 W</li> <li>■ Explosion proof: 12 to 250 V AC/DC</li> </ul>
<b>Performance</b>	<ul style="list-style-type: none"> <li>■ Measurement frequency: 600 KHz</li> <li>■ Repeatability: <math>\pm 1\%</math> of measurement</li> <li>■ Hysteresis: dependent on <math>\epsilon_r</math>; max. 2 mm (0.08") @ <math>\epsilon_r = 1.5</math></li> </ul>	
<b>Interface</b>		
Configuration	Locally using dip switches and potentiometers	<ul style="list-style-type: none"> <li>■ Remotely using SIMATIC PDM</li> <li>■ Locally using 3 button keypad (stand alone)</li> </ul>
Display	Transmitter with 3 LED indicators	Local digital LCD display
Communication		<ul style="list-style-type: none"> <li>■ PROFIBUS PA (IEC 61158 CPF3 CP3/2)</li> <li>■ Bus physical layer: IEC 61158-2 MBP(IS)</li> <li>■ Device profile: PROFIBUS PA profile for Process Control Devices Version 3.0, Class B</li> <li>■ FISCO field device</li> </ul>
Outputs	<ul style="list-style-type: none"> <li>■ Relay: 1 form 'C' (SPDT), non-inductive</li> <li>■ Solid state switch</li> <li>■ Time delay: 'on/off alarm' selectable</li> <li>■ Fail-safe operation (high or low)</li> <li>■ Delay timers: 2</li> </ul>	<ul style="list-style-type: none"> <li>■ Solid state switch</li> <li>■ Delay timers: 2 (Fall Time and Rise Time)</li> <li>■ Time delay: controlled by software</li> <li>■ Fail-safe operation (high or low)</li> <li>■ Relay or mA output: optional with added pcb board (stand alone)</li> </ul>
<b>Mechanical</b>		
Enclosure	<ul style="list-style-type: none"> <li>■ Powder coated aluminium with gasket</li> <li>■ Optional thermal isolator, 316 stainless steel (1.4404)</li> <li>■ Type 4 / NEMA 4 / IP65, IP68 optional</li> <li>■ Installation category: II</li> <li>■ Pollution degree: 4</li> </ul>	
Process connection	<ul style="list-style-type: none"> <li>■ 316 stainless steel (1.4404) (Standard and Cable)</li> <li>■ Thermal Isolator optional</li> </ul>	
Sensor	<ul style="list-style-type: none"> <li>■ PFA (Standard), stainless steel (1.4404) (Cable), 316L and ceramic (High Temperature)</li> <li>■ Max. 1 m (40") Standard sand High Temperature</li> <li>■ Max. 25 m (82 ft); stainless steel with FEP coating (Cable)</li> </ul>	
<b>Process conditions</b>		
Ambient temperature	-40 to 85 °C (-40 to 185 °F)	
Process temperature	<ul style="list-style-type: none"> <li>■ -40 to 200 °C (-40 to 392 °F) Standard</li> <li>■ -40 to 400 °C (-40 to 752 °F) High Temperature</li> </ul>	
Pressure	0 to 35 bar / 508 psi / 3500 kPa, gauge, nominal	-1 to 35 bar / 508 psi / 3500 kPa, gauge, nominal
Dielectric constant	$\epsilon_r$ : 1.5 minimum	
Location	Indoor/outdoor	
Altitude	2000 m (6562 ft) max.	
<b>Approvals</b>	CE, CSA <sup>WRTUC</sup> , FM, ATEX, WHG/VbF overfill protection (Germany), Vlare, Lloyd's Register of Shipping, categories ENV1, ENV2, and ENV5	

Specifications are subject to change without notice.  
 Pointek is a registered trademark of Siemens Milltronics Process Instruments Inc.  
 SIMATIC PDM is a registered trademark of Siemens AG.  
 © Siemens Milltronics Process Instruments Inc. 2005.



Certification No. 002284

## Million in one

Signal processing with field experience

Siemens level measurement instruments come with extensive field experience. Siemens Milltronics developed the signal processing technology for level instruments based on the experience of a million instruments in industrial applications.

With this experience we understand the importance of reliability, and we know what it takes to make a trusted and accurate level instrument for demanding applications. That's why our engineers invented the patented Active-Shield and Inverse Frequency capacitance technology, and that's why these instruments carry so many patents. With Siemens Milltronics you get the experience of a million applications in one instrument.

